



COMBINATA PIEGAFFERRI-CESOIA
COMBINED BENDING-CUTTING MACHINE
COUDEUSE-CISAILLE COMBINEE
COMBINADA

Dati Tecnici - Technical data Donnees Techniques Caracteristicas PTC 32-30	
Motore piegaferri Motor bending machine Moteur coudeuse Potencia motor dobladora	Hp 4
Motore cesoia Motor cutting machine Moteur cisaille Potencia motor cizallas	Hp 3
Lunghezza Lenght Longueur Longitud	mm1.060
Larghezza Width Largeur Anchura	mm900
Altezza Height Hauteur Altura	mm840
Peso Weight Poids Peso	Kg440

Cesoia - Cutting Machine Cisaille - Cizallas			
Res. Diam.	Ø	⊘	⊘
45 Kg/mm²	30	26x26	30x15
65 Kg/mm²	24	20x20	25x15
85 Kg/mm²	22	18x18	20x15

Piegaferri elettrico Concrete steel bending machine Coudeuse electrique pour fer à beton Dobladoras				
Giri/m R.P.M. Tours/m	N/barre N/bars N/barres N/barras	Res. 45 Kg/mm²	Res. 65 Kg/mm²	Res. 85 Kg/mm²
Diam. in mm.				
12	1	32	26	24
	2	22	18	16
	3	18	16	14
18	1	26	22	20
	2	18	16	14
	3	16	14	12



SILLA Macchine Edili e Stradali S.r.l.
53036 POGGIBONSI (SI) ITALY - Via San Gimignano, 96
Tel. +39.0577.938.051 - Fax +39.0577.981.609
e-mail: info@sillaitaly.com - www.sillaitaly.com